

DELIVERY & PICK UP
CATERING
MEDICAL
EVENTS



Made
in France



FUNCTIONAL

200 kg load and 1.3 m³ useful storage



PERFORMING

Up to 60 and 70 km of autonomy *



UNIQUE

Temperature maintenance down to -20° C



TECHNOLOGICAL

ATP FRA (positive) and FRC (negative) certified



RELIABLE

Recording of regulatory data (temperature curve and remote temperature monitoring)

DIMENSIONS

- Useful dimensions (mm)
L x W x H : 3 500 x 1 100 x 1 980
- Inside dimensions (mm)
L x W x H : 1 325 x 902 x 1 080
- Capacity of 12 boxes of 600 x 400 x 300 mm
- Carries an Europallet

STANDARD EQUIPMENT

- Door contactor for :
 - Door openings
 - Cutting off evaporator fans
 - Preventing restart in case of an open door
- Secure opening
- Rear camera
- Stainless steel handle
- Automatic interior LED lighting
- Bumper

OPTIONS

- ATP certificate
- Internal horizontal aluminum partition
- Customizable covering

VARIANTS

LMB POSITIVE COLD MODULE R 1234YF

- Positive cold down to 0°C
- Power : 400 W from 0°C +30°C
- ATP approval for 6 years, renewable for 6 years
- Rear door or double side doors



LMB NEGATIVE COLD MODULE

- Negative cold down to -20°C
- Power : 400 W down to -20°C
- ATP approval for 6 years, renewable for 6 years
- Rear door or double side doors



LMB ISOTHERMAL MODULE

- K coefficient approval : 0.31
- Rear door or double side doors



Discover our entire range



Refrigerated cell



Dry cell



Food cell



Deck cell



Waste cell



High pressure cleaner cell



* The autonomy depends on the loaded weight, interior and exterior temperatures, and the quality of pre-cooling.

The information and photos presented are for indicative purposes only, do not constitute contractual elements, and may be subject to subsequent modifications.



KLEUSTER
THE ENERGY OF A MOVING WORLD