



- DELIVERY & PICK UP
- CATERING
- MEDICAL
- EVENTS



FUNCTIONAL

200 kg load and 1.3 m³ useful storage



PERFORMING

Up to 60 and 70 km of autonomy*



UNIQUE

Temperature maintenance down to -20° C



TECHNOLOGICAL

ATP FRA (positive) and FRC (negative) certified



RELIABLE

Recording of regulatory data (temperature curve and remote temperature monitoring)

DIMENSIONS

- Useful dimensions (mm)
L x W x H : 3 500 x 1 100 x 1 980
- Inside dimensions (mm)
L x W x H : 1 325 x 902 x 1 080
- Capacity of 12 boxes of 600 x 400 x 300 mm
- Carries an Europallet

STANDARD EQUIPMENT

- Door contactor for :
 - Door openings
 - Cutting off evaporator fans
 - Preventing restart in case of an open door
- Secure opening
- Rear camera
- Stainless steel handle
- Automatic interior LED lighting
- Bumper

OPTIONS

- ATP certificate
- Internal horizontal aluminum partition
- Customizable covering

VARIANTS

LMB POSITIVE COLD MODULE R 1234YF

- Positive cold down to 0°C
- Power : 400 W from 0°C +30°C
- ATP approval
- Rear door or double side doors



LMB NEGATIVE COLD MODULE

- Negative cold down to -20°C
- ATP approval
- Rear door or double side doors



LMB ISOTHERMAL MODULE

- Rear door or double side doors
- K coefficient approval 0.31 for rear door and 0,36 for double side door



Discover our entire range



Refrigerated cell



Dry cell



Food cell



Deck cell



Waste cell



High pressure cleaner cell



KLEUSTER.COM

* The autonomy depends on the loaded weight, interior and exterior temperatures, and the quality of pre-cooling.

The information and photos presented are for indicative purposes only, do not constitute contractual elements, and may be subject to subsequent modifications.



KLEUSTER
THE ENERGY OF A MOVING WORLD