

**DELIVERY & PICK UP**  
**CATERING**  
**MEDICAL**  
**EVENTS**



Made  
in France



#### FUNCTIONAL

200 kg load and 1.3 m<sup>3</sup> useful storage



#### PERFORMING

Up to 60 of autonomy \*



#### UNIQUE

Temperature maintenance down to -20° C



#### TECHNOLOGICAL

ATP FRA (positive) certified



#### RELIABLE

Recording of regulatory data (temperature curve and remote temperature monitoring)

### DIMENSIONS

- Useful dimensions (mm)  
L x W x H : 3 500 x 1 100 x 1 890
- Inside dimensions (mm)  
L x W x H : 1 325 x 902 x 1 080
- Capacity of 12 boxes of 600 x 400 x 300 mm
- Carries an Europallet

### STANDARD EQUIPMENT

- Door contactor for :
  - Door openings
  - Cutting off evaporator fans
  - Preventing restart in case of an open door
- Secure opening
- Rear camera
- Stainless steel handle
- Automatic interior LED lighting
- Bumpers

### OPTIONS

- ATP certificate
- Interior horizontal aluminium partition
- Customizable covering

## VARIANTS

### LMB POSITIVE COLD MODULE R 1234YF

- Positive cold down to 0°C
- Power : 400 W from 0°C +30°C
- ATP approval
- Rear door or double side doors



### LMB NEGATIVE COLD MODULE

- Negative cold down to -20°C
- Rear door or double side doors



### LMB ISOTHERMAL MODULE

- Rear door or double side doors
- K coefficient approval 0.31 for rear door and 0,36 for double side door



Discover our entire range



\* The autonomy depends on the loaded weight, interior and exterior temperatures, and the quality of pre-cooling.

The information and photos presented are for indicative purposes only, do not constitute contractual elements, and may be subject to subsequent modifications.





**KLEUSTER**  
THE ENERGY OF A MOVING WORLD