KLEUSTER

A reliable, durable, and cost-effective range



BOX









BOX 350

Load capacity:

Up to 150 kg of load and 1.5 m^3 of usable volume

Range:

Up to 35 km of range*

Maneuverability:

Turning radius of 2.4m







Configurations:

- Modular interior fittings
- · Rear and right side doors



BOX FREEGÔNES

Load capacity:

Up to 300 kg of load and 2m³ of usable volume

Range:

Up to 80 km of range*

Security:

Hill-start assist







*on a single battery charge

Configurations:

- · Rear door and right side door
- · Right side curtain





ASSEMBLY

Renault Trucks assembles our cargo bikes at its Saint-Priest factory



SERVICE

Sales and maintenance of the bikes through the distributor network

KLEUSTER

A reliable, durable, and cost-effective range

BOX 350

BOX FREEGÔNES



EN 17860

250 W

Safety and riding

Battery type	Swappable	Fixed
Battery capacity	1.5 kWh	5.2 kWh
Battery technology	Iron Phosphate	Iron Phosphate
Charging via standard socket 16A 220V 50Hz	Yes	Yes
Downhill energy regeneration	Yes	Yes
Transmission type	Chainless crankset	Belt
Motor	Hub motor	Brushless
Maximum continuous rated power	2 x 125 W	250 W
Mechanical parking brake	Yes	Yes
Electric parking brake	Optional	Yes
Front and rear hydraulic disc brakes	Yes	Yes
Rear-view mirror	Mirrors	Cameras
Lighting system (front and rear lights, brake light, turn signals)	Yes	Yes
Reversing warning sound	Optional	Yes
Reversing radar	Optional	No
Hill-start assist	Optional	Yes

Equipment and comfort

Roof	Optional	Yes
Front protection	Short windshield	Integral bubble
Fork	Suspended	Suspended
Rear shock absorber	Yes	No
Comfort saddle	Yes	Yes
Code unlocking	Yes	Yes
Walk mode	Yes	Yes
Pedal assist	5 levels	Fixed
Maximum assist speed	25 km/h	18 km/h
Display	4''	4.3''
Phone holder	Accessory	No

Load management

Mechanical opening (keys)	Yes	Yes
Door opening by RFID	Optional	No
Flat-bottom shelf	Optional	No
Interior light	Optional	No
Aero lashing rails	Optional	No
Height-adjustable shelf (only with aero lashing rails)	Optional	No



Developed in compliance with electric bike assistance standards



Dimensions (W x L): 1 m x 3 m



Dimensions (W x L): 1.1 m x 3.5 m